PRINTING SYSTEM

|	
Publication number:	JP2001219626
Publication date:	2001-08-14
Inventor:	KITAGAWA HIDEAKI
Applicant:	RICOH KK
Classification:	
- international:	*G06F3/12; B41J2/52; B41J29/38; G03G15/08;* *G06F3/12; B41J2/52; B41J29/38; G03G15/08;* (IPC1-7): B41J29/38; B41J2/52; G03G15/08; G06F3/12
- European:	
Application number:	JP20000030479 20000208
Priority number(s):	JP20000030479 20000208

Report a data error here

Abstract of JP2001219626

PROBLEM TO BE SOLVED: To obtain a high quality output while saving a toner by adjusting the concentration so as to reduce the toner adhesion amount in a previous stage of producing a bit map image. SOLUTION: A document is produced by a host computer 10 using an application software 11. The document is converted to data to be interpreted by a printer driver software 12, and transferred to a printer 20. The printer 20 inputs the data transferred from the host 10 into an input buffer 21. A printer controller interprets a command row accumulated in the input buffer 21. In the case it is color information, a concentration correction such as the BG/UCR, and the &gamma correction is executed in a color conversion module for the inputted color information so as to convert the same to a CMYBk value. In the case it is graphic information, the graphic image is developed on a bit ma memory according to the CMYBk value determined by the color conversion module. In the case the command is a printing start command, the bit map image developed so far is printed.

Data supplied from the *esp@cenet* database - Worldwide